

IGOR



60W	CCT
49W ▲	3000K
40W ▼	4000K
32W	5700K

NEW GENERATION LED LINEAR LIGHTS

CUSTOM POWER AND COLOR TEMPERATURE

LIGHTTEX

Light. Create. Impress.

40W	CCT
34W ▲	3000K
28W ▼	4000K
22W	5700K



STING

www.lightex.bg



LED LINEAR LIGHT IGOR - 60W

LIGHTEX

Light. Create. Impress.

Product code: 232AL0030487




9600 lm
60W ◀ **C**

We present to you the first of its kind LED linear luminaires with remarkable options for choosing and combining power rates and color temperature: You choose from four options of power rate of your lighting fixture and at the same time the color temperature can be selected from three options. This means that there are 12 different configurations from which to choose the best one .

Custom power:



CCT custom color temperature - warm, neutral or cool white light.



And more benefits and high-end components:



TRIDONIC
LED energy efficient dimmable driver with established quality.



Connection between the diffuser and housing for ease of settings and installation.



Kit for surface ceiling installation and hooks for hanging.

LED
lamp

- Current: Input 420mA/ output 350mA
- Dimensions: 1480 x 85 x 71 mm
- Color: gray
- Material: polycarbonate

www.lightex.bg





LED LINEAR LIGHTIGOR - 40W

LIGHTEX

Light. Create. Impress.

Product code: 232AL0030482



6400 lm
40W **C**

- With 160 lm/W light output, dust and moisture protection IP65 and 50000 hours of life, IGOR LED luminaires are highly efficient and reliable.
- They have an optimal power factor PF >0.9 for real reading and pricing of consumed electricity.
- IGOR fixtures can be additionally assembled with emergency unit 5-200W LIGHTEX with order code: 907AL0000150.

- The polycarbonate diffuser prevents blinding and creates a different aesthetics of the premises.
- With metal ribbed clips.

Custom power:



CCT custom color temperature - warm, neutral or cool white light.




3000K



4000K



5700K



And more benefits and high-end components:



TRIDONIC
LED energy efficient dimmable driver with established quality.



Connection between the diffuser and housing for ease of settings and installation.



Kit for surface ceiling installation and hooks for hanging.

LED
lamp

- Current: Input 280mA/Output 350mA
- Dimensions: 1180 x 85 x 71 mm
- Color: gray
- Material: polycarbonate

www.lightex.bg





LED LINEAR LIGHT STING - 40W

LIGHTEX

Light. Create. Impress.

Product code: 232AL0030502

5200 lm
40W **F**



- With 130 lm/W efficiency, dust and moisture protection IP65 and 50.000 hours life span, the STING LED fixture is a reliable illuminator for long-term operation.
- PF>0.9 - high power factor for optimal pricing of the used electricity.
- 18 units can be connected in one line. bodies, which is just over 23m in length.

Custom power:



- Current: Input 280mA/ output 700mA
- Dimensions: 1280 x 90 x80 mm
- Color: white
- Material: polycarbonate

CCT custom color temperature - warm, neutral or cool white light.




3000K



4000K



5700K



And more benefits and high-end components:



TRIDONIC
LED energy efficient dimmable driver with established quality.



When connected in line, the line between the fixtures is almost invisible.



Set for quick and easy inline connection with connector



Isolated cable fitting

LED
lamp

www.lightex.bg

